

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).  
Date of Issue: 11/06/2020 Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

**Additional Information:** As shipped this product is a solid board/panel/sheet, is physiologically inert in its solid form, and does not pose a hazard as defined under the competent authority regulations. However, under normal conditions of use and installation user-generated dust may pose health and physical hazards. The hazards denoted in this SDS are for the downstream processing of these products when dust is generated.

#### 1.2. Intended Use of the Product

Exterior/interior structural/non-structural sheathing, subflooring, underlayment. Use in accordance with manufacturer's recommendations. See material storage, handling and installation guide(s).

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Huber Engineered Woods, LLC  
10925 David Taylor Drive  
Charlotte, NC  
United States  
Telephone (General): 704-548-5400  
[www.huberwood.com](http://www.huberwood.com)  
[www.exacor.com](http://www.exacor.com)

#### 1.4. Emergency Telephone Number

**Emergency Number** : CHEMTREC: 800-424-9300 or 703-527-3887 International

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Resp. Sens. 1	H334
Skin Sens. 1	H317
Carc. 1A	H350
STOT RE 1	H372

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)

:



GHS08

##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled.  
H350 - May cause cancer (inhalation).  
H372 - Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe dust.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P270 - Do not eat, drink or smoke when using this product.  
 P272 - Contaminated work clothing should not be allowed out of the workplace.  
 P280 - Wear protective gloves, protective clothing, and eye protection.  
 P284 - [In case of inadequate ventilation] wear respiratory protection.  
 P302+P352 - IF ON SKIN: Wash with plenty of water.  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+P313 - If exposed or concerned: Get medical advice/attention.  
 P314 - Get medical advice/attention if you feel unwell.  
 P321 - Specific treatment (see section 4 on this SDS).  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 - If eye irritation persists: Get medical advice/attention.  
 P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
 P362+P364 - Take off contaminated clothing and wash it before reuse.  
 P405 - Store locked up.  
 P501 - Dispose of contents/container in accordance with local, regional, national, provincial, territorial, and international regulations.

### Supplemental Information

: Avoid generating dust.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Magnesium oxide (MgO)	Calcined magnesite / Magnesium oxide / MAGNESIUM OXIDE / Magnesia	(CAS-No.) 1309-48-4	30 – 60	Not classified
Magnesium chloride	Magnesium chloride (MgCl <sub>2</sub> ) / MAGNESIUM CHLORIDE / Magnesium chloride, anhydrous / Magnesium dichloride / Magnesium chloride anhydrous / magnesium chloride anhydrous	(CAS-No.) 7786-30-3	30 – 60	Not classified
Dolomite (CaMg(CO <sub>3</sub> ) <sub>2</sub> )	Dolomite / Magnesium calcium carbonate / Calcium magnesium carbonate / DOLOMITE / DOLOMITE POWDER	(CAS-No.) 16389-88-1	4 – 14	Not classified
Wood dust, all soft and hard woods	Wood dust / Wood dust, all soft and hard woods, except western red cedar / Wood dust, nonallergenic / Wood dust, hard and soft / Wood dust (non-allergenic) / Wood dust, softwoods and hardwoods, except western red cedar / Wood / Wood dusts / Wood dusts (all other species) / Wood dust, all soft and hard woods, except red cedar / WOOD POWDER	(CAS-No.) Not applicable	2 – 12	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372 Comb. Dust

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Perlite	PERLITE	(CAS-No.) 130885-09-5	1 – 6	Not classified
Phosphate ion	Phosphate / Phosphate anion / Orthophosphate / Diammonium hydrogenorthophosphate	(CAS-No.) 14265-44-2	≤ 3	Not classified
Glass, oxide, chemicals	Glass, oxide / Glass / Sodium calcium polyphosphate / Glass powder / Calcium sodium polyphosphate / Sodium calcium polyphosphate silicate / Sodium zinc potassium polyphosphate / Glass flake / Calcium aluminum borosilicate / Glass dust / GLASS / Fiberglass / CALCIUM ALUMINUM BOROSILICATE	(CAS-No.) 65997-17-3	1 – 3	Not classified

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** For particulates and dust: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** For particulates and dust: Brush off loose particles from skin. Wash affected area with soap and water for at least 15 minutes. Should skin irritation, allergic reaction, or rash occur, remove contaminated clothing (if required) and seek medical advice.

**Eye Contact:** For particulates and dust: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** This product is not hazardous in the form in which it is shipped by the manufacturer. For particulates and dust: Causes skin irritation. Causes serious eye irritation. Skin sensitization. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer (inhalation). Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).

**Inhalation:** For particulates and dust: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.

**Skin Contact:** For particulates and dust: Causes skin irritation. May cause an allergic skin reaction. Repeated or prolonged contact will cause mechanical irritation.

**Eye Contact:** Causes serious eye irritation. May cause mechanical eye irritation.

**Ingestion:** Not expected to be a primary route of exposure. Ingestion may cause adverse effects.

**Chronic Symptoms:** For particulates and dust: May cause cancer by inhalation. Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation). Prolonged inhalation of wood dust is known to cause cancer of the respiratory system and lung disease.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures. When processed, the product dust is combustible. Use care during processing to minimize generation of dust.

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Explosion Hazard:** Product is not explosive. Contains substances that are combustible dusts. If the product is processed and dusts are generated and become dispersed with an ignition source, this may cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Magnesium oxides. Chlorine oxides. Chlorine. Hydrogen chloride. Phosphorus oxides. Calcium oxides.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid contact with skin, eyes and clothing. Do not breathe dust. Do not handle until all safety precautions have been read and understood.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. As shipped: Mechanically recover the product. For particulates and dust: Recover the product by vacuuming, shoveling or sweeping. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Avoid dust production. This product is inert in its massive form. However, user generated dust can pose health hazards described within this document.

**Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Do not breathe dust. Avoid generating and spreading dust, use score and snap instead of dry sawing when possible, this method generates less respirable dust. Use appropriate personal protective equipment (PPE).

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash contaminated clothing before reuse.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. hydrocarbons. Alkalis. Copper and its alloys. Halogenated compounds.

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

## 7.3. Specific End Use(s)

Exterior/interior structural/non-structural sheathing, subflooring, underlayment. Use in accordance with manufacturer's recommendations. See material storage, handling and installation guide(s).

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

<b>Magnesium oxide (MgO) (1309-48-4)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (fume, total particulate)
USA IDLH	US IDLH (mg/m <sup>3</sup> )	750 mg/m <sup>3</sup> (fume)
Alberta	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
British Columbia	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (respirable dust and fume)
British Columbia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
Nunavut	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
Ontario	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable particulate matter)
Québec	VEMP (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable dust)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup> (inhalable fraction)
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (inhalable fraction)
Yukon	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
Yukon	OEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (fume)
<b>Glass, oxide, chemicals (65997-17-3)</b>		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> total dust, 5 mg/m <sup>3</sup> , respirable fraction 8 hr
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3 fibers/cm <sup>3</sup> (fibers ≤3.5 μm in diameter & ≥10μm in length), TWA 5mg/m <sup>3</sup> (total)
Yukon	OEL TWA (mg/m <sup>3</sup> )	30 mppcf (dust or fibrous) 10 mg/m <sup>3</sup> (dust or fibrous)
<b>Wood dust, all soft and hard woods</b>		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (total)
Québec	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (except red cedar, containing no Asbestos and <1% Crystalline silica-total dust)
Yukon	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (non-allergenic) 5 mg/m <sup>3</sup> (allergenic, including cedar, mahogany, teak)
Yukon	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (non-allergenic) 2.5 mg/m <sup>3</sup> (allergenic, including cedar, mahogany, teak)

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Personal Protective Equipment:** Not generally required. The use of personal protective equipment may be necessary as conditions warrant. Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: White/off-white, solid board/panel/sheet material.
Odor	: None
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Water: Non-soluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Hydrocarbons. Alkalis. Copper and its alloys. Halogenated compounds.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO<sub>2</sub>). Oxides of magnesium. Chlorine oxides. Chlorine. Hydrogen chloride. Ammonia. Phosphorus oxides. Calcium oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** May cause cancer (inhalation).

**Specific Target Organ Toxicity (Repeated Exposure):** Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation).

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** For particulates and dust: Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.

**Symptoms/Injuries After Skin Contact:** For particulates and dust: Causes skin irritation. May cause an allergic skin reaction. Repeated or prolonged contact will cause mechanical irritation.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation. May cause mechanical eye irritation.

**Symptoms/Injuries After Ingestion:** Not expected to be a primary route of exposure. Ingestion may cause adverse effects.

**Chronic Symptoms:** For particulates and dust: May cause cancer by inhalation. Causes damage to organs (lungs) through prolonged or repeated exposure (inhalation). Prolonged inhalation of wood dust is known to cause cancer of the respiratory system and lung disease.

## 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

<b>Magnesium oxide (MgO) (1309-48-4)</b>	
LD50 Oral Rat	3870 mg/kg
<b>Magnesium chloride (7786-30-3)</b>	
LD50 Oral Rat	2800 mg/kg
LD50 Dermal Rat	> 2000 mg/kg (No deaths)
<b>Glass, oxide, chemicals (65997-17-3)</b>	
IARC Group	3
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.
<b>Wood dust, all soft and hard woods</b>	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Not classified.

<b>Magnesium chloride (7786-30-3)</b>	
LC50 Fish 1	1970 – 3880 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	140 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

### 12.2. Persistence and Degradability

<b>EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment</b>	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

<b>EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment</b>	
Bioaccumulative Potential	Not established.

# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Dolomite (CaMg(CO3)2) (16389-88-1)</b>	
<b>BCF Fish 1</b>	(no known bioaccumulation)

## 12.4. Mobility in Soil

<b>EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment</b>	
<b>Ecology - Soil</b>	Not established.

## 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Recycle the material as far as possible.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

- 14.1. In Accordance with DOT** Not regulated for transport
- 14.2. In Accordance with IMDG** Not regulated for transport
- 14.3. In Accordance with IATA** Not regulated for transport
- 14.4. In Accordance with TDG** Not regulated for transport


## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Carcinogenicity Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
<b>Magnesium oxide (MgO) (1309-48-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Magnesium chloride (7786-30-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Phosphate ion (14265-44-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Glass, oxide, chemicals (65997-17-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Dolomite (CaMg(CO3)2) (16389-88-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

#### California Proposition 65

 **WARNING:** This product can expose you to Wood dust, all soft and hard woods, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Wood dust, all soft and hard woods	X			

<b>Magnesium oxide (MgO) (1309-48-4)</b>	
U.S. - Massachusetts - Right To Know List	



# EXACOR(TM) Sheathing, EXACOR(TM) Subfloor, EXACOR(TM) Underlayment

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

### Wood dust, all soft and hard woods

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

### 15.3. Canadian Regulations

#### Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

#### Magnesium chloride (7786-30-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Phosphate ion (14265-44-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### Glass, oxide, chemicals (65997-17-3)

Listed on the Canadian DSL (Domestic Substances List)

#### Dolomite (CaMg(CO<sub>3</sub>)<sub>2</sub>) (16389-88-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 11/06/2020

### Revision

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Resp. Sens. 1	Respiratory sensitization, Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)